



B Series Injectors

Water Pressure (PSI)	Operating Range - Gallons Per Minute (GPM)			
	202B	203B	204B	206B
10	.25 - 2	.5 - 3.5	2 - 6.4	3.6 - 11
20	.3 - 2.3	.55 - 4.4	2.3 - 7.5	4.2 - 13
40	.37 - 2.9	.7 - 5.4	2.9 - 9.5	5.3 - 17
60	.43 - 3.4	.8 - 6.4	3.4 - 11	6.2 - 19
100	.54 - 4.2	1 - 8	4.2 - 14	7.7 - 24
200	.73 - 5.7	1.4 - 11	5.7 - 19	11 - 33
400	1 - 7.9	1.9 - 15	7.9 - 26	15 - 46
500	1.2 - 8.9	2.1 - 17	8.9 - 29	17 - 51
700*	1.4 - 11	2.5 - 20	11 - 35	20 - 60
1000*	1.6 - 13	3 - 23	13 - 41	23 - 70
1500*	2 - 16	3.5 - 28	16 - 50	28 - 87
2000*	2.2 - 18	4.7 - 37	18 - 58	33 - 100
3000*	2.7 - 20	5 - 45	20 - 70	40 - 100

* - Specify = S Stainless Steel Knob - Part # 24-32S or Part # 24-32ST (for tips) for pressures exceeding 700psi



B Series Injectors Dilution Rates

Metering Tip	Injection Rates (OZ Per Minute)											
	202BT			203BT			204BT			206BT		
	1 cps	75 cps	200cps	1 cps	75 cps	200cps	1 cps	75 cps	200cps	1 cps	75 cps	200cps
Tan	1	1	0.6	1.1	0.8	0.5	1.1	0.8	0.5	1	0.7	0.6
Orange	1.5	1.2	0.7	1.4	1	0.7	1.4	0.9	0.6	1.4	1	0.8
Turquoise	1.8	1.4	1.2	2	1.4	1	1.9	1.2	0.9	1.9	1.3	1
Pink	2.5	2	1.4	2.7	1.8	1.3	2.6	1.7	1.3	2.6	1.8	1.3
Lt. Blue	3.2	2.7	1.7	3.5	2.4	1.6	3.4	2.4	1.6	3.5	2.3	1.7
Brown	3.3	2.9	1.9	4	2.7	1.7	4	2.4	1.9	4	2.6	1.8
Red	4.2	3	2.1	4.9	3.3	2	4.9	2.9	2.2	5	3.1	2
White	4.8	3.5	2.1	6	3.9	2.3	6	3.4	2.4	6.2	3.7	2.4
Green	5.2	3.7	2.3	6.8	4.4	2.5	6.8	3.8	2.5	7.1	4.1	2.6
Blue	6.2	4	2.4	7.8	4.9	2.7	8.4	4.3	3.1	8.9	4.8	2.9
Yellow	7	4.3	2.7	10.3	5.9	2.9	13.1	5.2	3.4	13.5	5.9	3.2
Black	7.1	4.4	2.8	13.2	6.7	3	18.2	6.1	3.5	20.1	6.7	3.5
Purple	7.4	4.6	2.9	17.1	6.7	3.1	27.5	6.8	3.5	31.3	7.5	3.6
Gray	7.8	4.7	3.1	19	7.1	3.3	32.9	7	3.5	38.3	8	3.8
No Tip	7.9	4.7	3.3	20	8	3.7	39.8	7.9	3.7	48.1	9.2	4.4