



Specification Chart

ag.demaeng.com



The Quick Specifications Chart is designed to allow you to compare our range of injectors at a glance

MODEL	FLOW RATE	PRESSURE	PERCENT	RATIO	OZ/GALLON	ML/GALLON	CONNECTION
566AG	.09 – 11 GPM (3.4 - 41.6 LPM)	2.9-120 PSI	1%	1:100 FIXED	1.28	38.4	3/4" NPT
568AG	.09 – 11 GPM (3.4 - 41.6 LPM)	2.9-120 PSI	0.80%	1:128 FIXED	1	30	3/4" NPT
569CWONOFF	.09 – 11 GPM (3.4 - 41.6 LPM)	2.9-120 PSI	.1-.9%	1:1000 – 1:111	.128 - 1.15	3.84 - 34.5	3/4" NPT
569PVDFONOFF	.09 – 11 GPM (3.4 - 41.6 LPM)	2.9-120 PSI	.1-.9%	1:1000 – 1:111	.128 - 1.15	3.84 - 34.5	3/4" NPT
570CW & 571CW	.09 – 11 GPM (3.4 - 41.6 LPM)	2.9-120 PSI	.3-2%	1:333 - 1:50	.4 - 2.56	12 - 76.8	3/4" NPT
570PVDF & 571PVDF	.09 – 11 GPM (3.4 - 41.6 LPM)	2.9-120 PSI	.3-2%	1:333 - 1:50	.4 - 2.56	12 - 76.8	3/4" NPT
572CW & 573CW	.09 – 11 GPM (3.4 - 41.6 LPM)	2.9-120 PSI	.4-4%	1:250 - 1:25	.5 - 5.12	15 - 153.6	3/4" NPT
572PVDF & 573PVDF	.09 – 11 GPM (3.4 - 41.6 LPM)	2.9-120 PSI	.4-4%	1:250 - 1:25	.5 - 5.12	15 - 153.6	3/4" NPT
TF3.002ON/OFF	.13 - 14 GPM (.5 - 53 LPM)	2.9-120 PSI	.3-2%	1:333 - 1:50	.4 - 2.56	12 - 76.8	1" NPT
TF3.004ON/OFF	.13 - 14 GPM (.5 - 53 LPM)	2.9-120 PSI	.4-4%	1:250 - 1:25	.5 - 5.12	15 - 153.6	1" NPT
1400A & 1400M	.13 – 14 GPM (.5 - 53 LPM)	2.9-120 PSI	.03-.2%	1:3000 - 1:500	.04 - .25	1.2 - 7.5	3/4" NPT
1401A & 1401M	.13 - 14 GPM (.5 - 53 LPM)	2.9-120 PSI	.1-.9%	1:1000 - 1:111	.128 - 1.15	3.84 - 34.5	3/4" NPT
1402A & 1402M	.13 – 14 GPM (.5 - 53 LPM)	2.9-120 PSI	.3-2%	1:333 - 1:50	.4 - 2.56	12 - 76.8	3/4" NPT

MODEL	FLOW RATE	PRESSURE	PERCENT	RATIO	OZ/GALLON	ML/GALLON	CONNECTION
1405A & 1405M	.13 – 14 GPM (.5 - 53 LPM)	2.9-120 PSI	1-5%	1:100 - 1:20	.64 - 6.4	19.2 - 192	3/4" NPT
1410A & 1410M	.13 – 14 GPM (.5 - 53 LPM)	2.9-120 PSI	1-10%	1:100 - 1:10	1.28 - 12.8	38.4 - 384	3/4" NPT
TF.5.001CL.PAAON/OFF	.8 - 22 GPM (3 - 83.3 LPM)	14.7-120 PSI	.1-1%	1:1000-1:100	.13 - 1.28	3.9 - 38.4	1" NPT
TF.5.002ON/OFF	.8 - 22 GPM (.3 - 83.3 LPM)	14.7-120 PSI	.2-2%	1:500-1:50	.26 - 2.56	7.8 - 76.8	1" NPT
TF.5.002.V.ON/OFF	.8 - 22 GPM (.3 - 83.3 LPM)	14.7-120 PSI	.2-2%	1:500-1:50	.26 - 2.56	7.8 - 76.8	1" NPT
TF.5.005ON/OFF	.8 - 22 GPM (.3 - 83.3 LPM)	14.7-120 PSI	1-5%	1:200-1:20	.64 - 6.4	19.2 - 192	1" NPT
TF.10.001CL.PAAON/OFF	2 - 45 GPM (7.5 - 170 LPM)	14.7-120 PSI	.1-1%	1:1000-1:100	.13 - 1.28	3.9 - 38.4	1.5" NPT
TF.10.002ON/OFF	2 - 45 GPM (7.5 - 170 LPM)	14.7-120 PSI	.2-2%	1:500 - 1:50	.26 - 2.56	7.8 - 76.8	1.5" NPT
TF.10.005ON/OFF	2 - 45 GPM (7.5 - 170 LPM)	14.7-120 PSI	1-5%	1:200 - 1:20	.64 - 6.4	19.2 - 192	1.5" NPT
TF.25.001CL.PAAON/OFF	9 - 110 GPM (34 - 416 LPM)	14.7 -120 PSI	.1-1%	1:1000 - 1:100	.13 - 1.28	3.9 - 38.4	2" NPT
TF.25.002ON/OFF	9 - 110 GPM (34 - 416 LPM)	14.7 -120 PSI	.3-2.5%	1:333 - 1:40	.38 - 3.20	11.4 - 96	2" NPT
TF.25.005ON/OFF	9 - 110 GPM (34 - 416 LPM)	14.7 -120 PSI	1-5.5%	1:100 - 1:20	1.28 - 6.40	38.4 - 192	2" NPT

Customer Service & Tech Support:
(800) 325-3362
(314) 966-3533
Sales@demaeng.com



ag.demaeng.com

Dema Engineering Company
10020 Big Bend Blvd.
St. Louis, MO 63122

